

## TECHNICAL SPECIFICATIONS

Grade	GLX						GLS	
	2.0L			2.4L			3.0L	
Wheel drive	2WD			4WD				
Transmission	CVT						6AT	
Seating	5		7		5		7	
Model code	GF2WXTSGL	GF2WXTMGL	GF2WXTMHZR	GF3WXTSHZL	GF3WXTMGZL GF3WXTMGZR	GF3WXTMHZL	GF4WXLXGZL	GF4WXLXYZL
<b>Dimensions and weights</b>								
Overall length	mm		4695					
Overall width	mm		1810					
Overall height	Without roof rail		1710					
	With roof rail		1710					
Wheelbase	mm		2670					
Track	Front		1540					
	Rear		1540					
Ground clearance (unladen)	mm		190					
Curb weight	Total		1430	1460	1530	1505	1535	1590
	Front		830	830	860	865		915
	Rear		600	630	670	640	670	675
Gross vehicle weight	kg		1985	2170	2210	2120	2210	2280
Gross axle weight	Front		1150					
	Rear		1250					
Seating capacity	persons		5		7		7	
<b>Performance</b>								
Max. speed	km/h		193			198		205
Acceleration	0-100 km/h		11.4		12.0		10.5	
	120-140 km/h		7.3		7.7		6.1	
	0-400 m		18.4		18.7		17.7	
Min. turning radius	m		5.3					
<b>Engine</b>								
Type (code)	DOHC MIVEC (4B11)			DOHC MIVEC (4B12)			SOHC MIVEC (6B31)	
Fuel type / octane	Unleaded / RON 90 and over*						Unleaded / RON 95 and over	
Total displacement	cc		1998			2360		2998
Bore x stroke	mm		86.0 x 86.0			88.0 x 97.0		87.6 x 82.9
Compression ratio			10.0					
Max. output (EEC net)	kW (PS)/rpm		107 (145)/6000			123 (167)/6000		169 (230)/6250
Max. torque (EEC net)	N·m (kg·m)/rpm		196 (20.0)/4200			222 (22.6)/4100		292 (29.8)/3750
<b>Fuel system</b>								
Fuel supply system	Electronically Controlled Injection							
Fuel tank capacity	liters		63			60		
<b>Electrical system</b>								
Alternator	V-Ah		12-105			12-120		
Starter	V-kW		12-1.3			12-1.4		
<b>Transmission</b>								
Type	CVT						6AT	
Gear ratio	D range		2.631-0.378					
	1st		-					
	2nd		-					
	3rd		-					
	4th		-					
	5th		-					
	6th		-					
	Reverse		1.960					
Final			6.026					
<b>Steering</b>								
Type	Rack and pinion (electric power assisted)							
<b>Suspensions</b>								
Front	MacPherson strut with coil springs and stabilizer bar							
Rear	Multi link with coil springs and stabilizer bar							
<b>Brakes</b>								
Front	Ventilated discs							
Rear	Discs							
<b>Tires and wheels</b>								
Tires (front and rear)	215/70R16						225/55R18	

\* Unleaded / RON 95 and over for models available in Azerbaijan.

Note: Hazardous driving may cause serious injury or vehicle damage. Please drive safely at all times.