

SPECIFICATIONS

MODEL	Body type		5-Door							
	Drive system		4WD							
	Engine		3.8 V6 MIVEC	3.0 V6			3.2 IC/TC DI-D	2.8 IC/TC diesel		
	Price class		GLS (GLX opt)	GL	GLS (GLX opt)	GLS (GLX opt)	GLS (GLX opt)	GL	GLS (GLX opt)	
Model code	LHD	EURO 2	V97WLYXYSL	V93WLNDVQL	—	V93WLRXVQL	V98WLYXZSL	—	—	
		EURO 4	V97WLYXYUL	—	V93WLYXVUL	—	—	—	—	
		R15-04	—	—	—	—	—	V96WLNDFL	V96WLNXFL	V96WLRXFL
	RHD	EURO 2	—	—	—	V93WLRXVQR	V98WLYXZSR	—	—	—
		R15-04	—	—	—	—	—	V96WLNDFR	V96WLNXFR	—
DIMENSIONS AND WEIGHTS	Overall length	mm	4,900							
	Overall width	mm	1,875 (GLX Package: 1,845)	1,845	1,875 (GLX Package: 1,845)	1,875 (GLX Package: 1,845)	1,875 (GLX Package: 1,845)	1,845	1,875 (GLX Package: 1,845)	
	Overall height	mm	1,870 (with roof rails: 1,900)							
	Wheelbase	mm	2,780							
	Ground clearance	mm	235							
	Curb weight	kg	2,155	2,025	2,105	2,105	2,250	2,065	2,155	2,150
	Gross vehicle weight	kg	2,765	2,720	2,720	2,720	2,865	2,740		
	Seating capacity	persons	7	9	7	7	7	9	7	
PERFORMANCE	Max. speed*1	km/h	200	175			174		155	
	Max. climbing ability	tanθ	0.7							
	Approach angle		36.6°							
	Ramp break-over angle		22.5°							
	Departure angle		25.0°							
	Min. turning radius	m	5.7							
ENGINE	Type (code)		3.8-liter 24-valve V6 SOHC MIVEC (6G75)	3.0-liter 24-valve V6 SOHC (6G72)			3.2-liter 16-valve inline-4 intercooled turbocharged DOHC diesel (4M41)	2.8-liter 8-valve inline-4 intercooled turbocharged SOHC diesel (4M40)		
	Displacement	cc	3,828	2,972			3,200	2,835		
	Max. output (EEC net)	kW (PS)/rpm	184 (250)/6,000*2	135 (184)/5,250*2	131 (178)/5,250*2	135 (184)/5,250*2	121 (165)/3,500	92 (125)/4,000		
	Max. torque (EEC net)	N-m (kg-m)/rpm	329 (33.5)/2,750*2	267 (27.2)/4,000*2	261 (26.6)/4,000*2	267 (27.2)/4,000*2	373 (38.1)/2,000	294 (30.0)/2,000		
FUEL SYSTEM	Fuel supply equipment		ECI-MULTI (Electronic Controlled Injection - Multi Point Injection)				Electronic Common Rail direct fuel injection	Indirect fuel injection		
	Fuel tank capacity	liters	88							
DRIVE SYSTEM	Type	Super Select 4WD II (SS4 II)								
TRANSMISSION	Type	INVECS-II 5-speed automatic with Sports Mode	5-speed manual	INVECS-II 5-speed automatic with Sports Mode	INVECS-II 4-speed automatic with Sports Mode	INVECS-II 5-speed automatic with Sports Mode	5-speed manual		4-speed automatic with Sports Mode	
STEERING	Type	Rack-and-pinion, power assisted								
SUSPENSIONS	Front	Double-wishbone, coil springs with stabilizer bar								
	Rear	Multi-link, coil springs with stabilizer bar								
BRAKES	Front	Ventilated discs (4-pot)	Ventilated discs (2-pot)			Ventilated discs (4-pot)		Ventilated discs (2-pot)		
	Rear	Ventilated discs								
TIRES	Front and rear	265/65R17 112H								

*1: Measured by MITSUBISHI MOTORS CORPORATION.

*2: Figures quoted without Pre-air cleaner.

Note: These specifications are subject to change without notice. Please consult your local Mitsubishi dealer/distributor for detailed specifications.